

NOMARK 66 : Capacitor discharge stud welding equipments

- This new line of Microprocessor controlled Capacitor Discharge stud welding equipments incorporates the latest solid state technology into a compact and rugged CD Stud Welder
- This unit has the capacity to weld studs ranging from 3 mm through 8 mm (10 mm) full flanged studs and pins (including cupped head pins)
- The monitoring of all functions is clearly displayed by LED on the front panel. The short charging cycles increase productivity.
- Inverter power modules replace traditional heavy transformer rectifiers, are more efficient to use and faster to charge.
- Lightweight and easily portable, the NOMARK 66 weighs in at around half of many other conventional studwelding equipment
- Thermostatically controlled cooling fan in NOMARK 88 for increased efficiency



Unit	NOMARK 66
Welding range	: M 3 - M 8 (M8 in Aluminum and Brass after welding tests)
Weldable Materials	: Steel, Stainless Steel, Aluminium, Brass
Welding process	: "Contact" and "GAP"
Capacitance	: 66.000 μ F
Charging	: 50-200 V (UP and DOWN)
Digital Voltmeter	: Yes
Duty cycle	: up till 30 studs/min
Energy	: 1.320 Ws
Mains supply	: 230 V - 50/60 Hz - 10 AT
Size (w x h x l)	: 195 x 265 x 400 mm
Weight	: 12 Kg

Esta-Rowell Engineering Pte Ltd

22 Woodlands Link #04-29 Singapore 738734

T: +65 6753 9959 | F: 6753 2653 | sinesta@pacific.net.sg



CONTACT & GAP stud welding guns

- Our Stud Guns are ergonomically designed for better hand fit and comfort (reduces operator fatigue for increased weld repeatability).
- Gun configured with tripod legs allow the welding of studs up to 40 mm long. Longer legs or extension kit available for longer studs
- Our Contact Stud Guns have a permanent internal spring with easy adjustment for various spring pressures allowing to apply the correct spring pressure to the weld
- G1: The lightest weight CD Gap Gun in the industry.



Gun	C1	G1
Welding range	: M 3 to M 8 (M 10)	M 3 to M 8 (M 10)
Stud Length	: 6 to 40 mm	6 to 40 mm
Pin Length	: up to 110 mm (with optional pins chuck) + 110 mm (with ISO Kit)	up to 100 mm (with optional pins chuck) + 100 mm (with ISO Kit)
Welding process	: Contact	Gap
Settings	: Infinitely adjustable	Infinitely adjustable
Cables length	: 5 meters	3 meters (highly flexible)
Weight	: 0,7 Kg. (without cable)	0,6 Kg. (without cable)